

This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.
 Customer to confirm current revision of drawing prior to ordering.

NO SHARP EDGES

98

22 Ø

22 Ø

82

3

13

5/8 UNC

Note Slight Undercut

16

Chemical Composition Limits		Alloy:	
Standard: AS2239* (Most current revision)		Z1	
Zinc			
Element	min.	max.	
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc	remainder		

* Corresponds to MIL-DTL-18001L alloy composition

Notes

1. Anodes are cast to comply with CAA's standard casting tolerances
2. All sharp edges removed for safe handling
3. Anode insert material to meet relevant Australian/International specifications



All dimensions are in mm (nominal)

Rev	Details of Change(s)	Date	Drawn	Verified
1	Cathodic Diecasting Original	14 Sept 2009	B.L.	R.G.
2	2013 Catalogue Version (CAA Logo)	25 March 2015	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
0.250	0.250

CAA
 Cathodic Anodes Australasia
 cathodicanodes.com.au

Product Zinc Anode	
Part no. CDZ9-138	Scale 1.5 : 1
Drawing No: CD1268	Rev Sheet 2 1 of 1
Drawn by: R Northey Date: 25 MAR 2015	

