





4 3 2  
COMBINATION SET - Individual Components Shown At Top - Plug Material: DEZINCIFICATION RESISTANT BRASS

1  
This drawing is the property of Cathodic Anodes Australasia. To be used with permission only. This drawing becomes an uncontrolled document once issued as hard or electronic copy. Customer to confirm current revision of drawing prior to ordering.



NO SHARP EDGES

 = Australian Made Logo

All dimensions are in mm (nominal)

Chemical Composition Limits			Alloy: <b>Z1</b>
Standard: AS2239* (Most current revision)			
Zinc			
Element	min.	max.	
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc		remainder	

\* Corresponds to MIL-DTL-18001L alloy composition

- Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
  2. All sharp edges removed for safe handling
  3. Anode insert material to meet relevant Australian/International specifications



Rev	Details of Change(s)	Date	Drawn	Verified
1	Cathodic Diecasting Original	03 May 2011	R.N.	R.G.
2	2013 Catalogue Version (CAA Logo)	14 April 2015	R.N.	R.G.
3	Stamping & Logo added to DR Brass Plug	17 Nov 2020	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
<b>0.030</b>	<b>0.050</b>



**CAA**  
Cathodic Anodes Australasia  
cathodicanodes.com.au

Product			
<b>Zinc Anode &amp; DR Brass Plug</b>			
Part no.	Scale		
<b>CDZ9-078</b>	<b>2 : 1</b>		
Drawing No:	Rev	Sheet	
<b>CD2101</b>	<b>3</b>	<b>1 of 1</b>	
Drawn by: R Northey	Date: 17 NOV 2020		