


COMBINATION SET - Individual Components Shown At Top - Plug Material: DEZINCIFICATION RESISTANT BRASS

This drawing is the property of Cathodic Anodes Australasia. To be used with permission only. This drawing becomes an uncontrolled document once issued as hard or electronic copy. Customer to confirm current revision of drawing prior to ordering.

Zinc Anode Only - CAA Part No: CDZ9-010 (Drawing No: CDQ-107)

D.R. Brass Plug 06 (BP06)




3/8 UNC

3/8 NPT

70

10 Ø



17

50

14

6

NO SHARP EDGES

△ = Australian Made Logo

All dimensions are in mm (nominal)

| Chemical Composition Limits | | |
|---|-----------|-------|
| Standard: AS2239* (Most current revision) | | |
| Zinc | | |
| Element | min. | max. |
| Cadmium | 0.025 | 0.07 |
| Aluminium | 0.10 | 0.50 |
| Silicon | - | 0.005 |
| Copper | - | 0.005 |
| Iron | - | 0.005 |
| Lead | - | 0.006 |
| Other Impurities | | |
| - each | - | 0.005 |
| - total | - | 0.02 |
| Zinc | remainder | |

Alloy: **Z1**

- Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
 2. All sharp edges removed for safe handling
 3. Anode insert material to meet relevant Australian/International specifications



| Nett Weight | | Gross Weight | | |
|--------------|--|---------------|-------|----------|
| Kg (nominal) | | Kg (nominal) | | |
| 0.030 | | 0.050 | | |
| Rev | Details of Change(s) | Date | Drawn | Verified |
| 1 | Cathodic Diecasting Original | 07 June 2011 | R.N. | R.G. |
| 2 | 2013 Catalogue Version (CAA Logo) | 15 April 2015 | R.N. | R.G. |
| 3 | Stamping & Logo added to DR Brass Plug | 10 Nov 2020 | R.N. | R.G. |

CAA
Cathodic Anodes Australasia
cathodicanodes.com.au

| Product | | | |
|---------------------------------------|-------------------|-------|---------------|
| Zinc Anode & DR Brass Plug | | | |
| Part no. | CDZ9-122 | Scale | 2 : 1 |
| Drawing No: | CD2122 | Rev | 3 |
| Drawn by: R Northey | Date: 10 NOV 2020 | Sheet | 1 of 1 |

* Corresponds to MIL-DTL-18001L alloy composition