





4 3 2 1
COMBINATION SET - Individual Components Shown At Top - Plug Material: DEZINCIFICATION RESISTANT BRASS

This drawing is the property of Cathodic Anodes Australasia. To be used with permission only. This drawing becomes an uncontrolled document once issued as hard or electronic copy. Customer to confirm current revision of drawing prior to ordering.



NO SHARP EDGES

 = Australian Made Logo

All dimensions are in mm (nominal)

Chemical Composition Limits			Alloy: Z1
Standard: AS2239* (Most current revision)			
Element	min.	max.	
Zinc			
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc	remainder		

* Corresponds to MIL-DTL-18001L alloy composition

- Notes**
1. Anodes are cast to comply with CAA's standard casting tolerances
 2. All sharp edges removed for safe handling
 3. Anode insert material to meet relevant Australian/International specifications



Rev		Details of Change(s)	Date	Drawn	Verified
1		Cathodic Diecasting Original	07 June 2011	R.N.	R.G.
2		2013 Catalogue Version (CAA Logo)	21 February 2014	R.N.	R.G.
3		Stamping & Logo added to DR Brass Plug	10 Nov 2020	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
0.030	0.050



CAA
Cathodic Anodes Australasia

cathodicanodes.com.au

Product	
Zinc Anode	
Part no. CDZ9-125	Scale 2 : 1
Drawing No: CD2123	Rev 3 Sheet 1 of 1
Drawn by: R Northey Date: 10 NOV 2020	