


This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.
 Customer to confirm current revision of drawing prior to ordering.

40




80



200

40



Chemical Composition Limits			Alloy: Z1
Standard: AS2239* (Most current revision)			
Element	min.	max.	
Zinc			
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc		remainder	

* Corresponds to MIL-DTL-18001L alloy composition

- Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
 2. All sharp edges removed for safe handling
 3. Anode insert material to meet relevant Australian/International specifications



Rev	Details of Change(s)	Date	Drawn	Verified
1	For Manufacture	24 Feb 2017	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
2.50	N/A

CAA
Cathodic Anodes Australasia

cathodicanodes.com.au

Product	
Zinc Anode	
Part no.	Scale
CDZ3-8 Type1 2.5 kg	1 : 1.75
Drawing No: CD2354	Rev Sheet
	1 1 of 1
Drawn by: R Northey	Date: 24 FEB 2017
Mould No:	Strap Sample: N/A

All dimensions are in mm (nominal)