

This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.  
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.  
 Customer to confirm current revision of drawing prior to ordering.

4

3

2

1

12

65 Ø

65 Ø

Thru Hole

5.5

12 \*

38 I/D

\* Suggest Fastener Head Is Limited 10 mm Ø

48 CRS

12

Insert Plate  
 65 O/D, 38 I/D, x 1.5 mm  
 Galvanised Steel Disc

Chemical Composition Limits			Alloy: <b>Z1</b>
Standard: AS2239* (Most current revision)			
Zinc			
Element	min.	max.	
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc	remainder		

\* Corresponds to MIL-DTL-18001L alloy composition

Notes


1. Anodes are cast to comply with CAA's standard casting tolerances
2. All sharp edges removed for safe handling
3. Anode insert material to meet relevant Australian/International specifications

Rev	Details of Change(s)	Date	Drawn	Verified
1	New Item	21 March 2018	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
<b>0.095</b>	<b>0.115</b>



**CAA**  
 Cathodic Anodes Australasia  
 cathodicanodes.com.au

Product <b>Zinc Anode</b>	
Part no. <b>CDZ9 - 200</b>	Scale <b>1 : 1</b>
Drawing No: <b>CD2450</b>	Rev <b>1</b> Sheet <b>1 of 1</b>
Drawn by: R Northey Date: 21 MAR 2018	
Mould No: N/A Tooling: N/A	

All dimensions are in mm (nominal)

4

3

2

1