


This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.
 Customer to confirm current revision of drawing prior to ordering.



INSERT - 25 x 3 ALUMINIUM FLAT

Chemical Composition Limits		Alloy:
Standard: AS2239* (Most current revision)		Z1
Zinc		
Element	min.	max.
Cadmium	0.025	0.07
Aluminium	0.10	0.50
Silicon	-	0.005
Copper	-	0.005
Iron	-	0.005
Lead	-	0.006
Other Impurities		
- each	-	0.005
- total	-	0.02
Zinc	remainder	

* Corresponds to MIL-DTL-18001L alloy composition

- Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
 2. All sharp edges removed for safe handling
 3. Anode insert material to meet relevant Australian/International specifications



Rev	Details of Change(s)	Date	Drawn	Verified
1	2019 Catalogue Version	17 NOV 2020	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
1.60	1.70

CAA
Cathodic Anodes Australasia
cathodicanodes.com.au

Product Zinc Anode		All dimensions are in mm (nominal)	
Part no. CDZ3-7 ALS 1.7 kg	Scale 1 : 1.75	Rev 1	Sheet 1 of 1
Drawing No: CD2610		Drawn by: R Northey Date: 17 NOV 2020	
Mould No: 73	Strap Sample: 16		

