


This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.
 Customer to confirm current revision of drawing prior to ordering.



INSERT - 25 x 3 ALUMINIUM FLAT

Chemical Composition Limits			Alloy:
Standard: AS2239* (Most current revision)			Z1
Zinc			
Element	min.	max.	
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc	remainder		

* Corresponds to MIL-DTL-18001L alloy composition

- Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
 2. All sharp edges removed for safe handling
 3. Anode insert material to meet relevant Australian/International specifications



Nett Weight		Gross Weight		
Kg (nominal)		Kg (nominal)		
2.40		2.50		
Rev	Details of Change(s)	Date	Drawn	Verified
1	2019 Catalogue Version	17 NOV 2020	R.N.	R.G.

CAA
 Cathodic Anodes Australasia
cathodicanodes.com.au

Product		Zinc Anode	
Part no.	CDZ3-93-15 ALS	Scale	1 : 1.75
Drawing No:	CD2614	Rev	1
		Sheet	1 of 1
Drawn by: R Northey	Date: 17 NOV 2020		
Mould No: 76	Strap Sample: 16		

All dimensions are in mm (nominal)