

This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.
 Customer to confirm current revision of drawing prior to ordering.

Plan View

1700

Side View

1524

1512

End View - Scale 1 : 2

40

38

33

Insert - 12 Ø Mild Steel Round Bar

All dimensions are in mm (nominal)

Chemical Composition Limits		Alloy:
Standard: AS2239* (Most current revision)		Z1
Element	min.	max.
Cadmium	0.025	0.07
Aluminium	0.10	0.50
Silicon	-	0.005
Copper	-	0.005
Iron	-	0.005
Lead	-	0.006
Other Impurities		
- each	-	0.005
- total	-	0.02
Zinc	remainder	

* Corresponds to MIL-DTL-18001L alloy composition

Notes

1. Anodes are cast to comply with CAA's standard casting tolerances
2. All sharp edges removed for safe handling
3. Anode insert material to meet relevant Australian/International specifications



Rev	Details of Change(s)	Date	Drawn	Verified
1	Cathodic Diecasting Original	20 September 2010	B.L.	R.G.
2	Amended Bottom Width	15 March 2011	B.L.	R.G.
3	2013 Catalogue Version (CAA Logo)	03 November 2014	R.N.	R.G.

Nett Weight	Gross Weight
Kg (nominal)	Kg (nominal)
12.5	14.0



cathodicanodes.com.au

Product		Zinc Anode	
Part no.	CDZ8-60S 14 kg	Scale	1 : 7.5
Drawing No:	CD1416	Rev	3
		Sheet	1 of 1
Drawn by: R Northey	Date: 03 NOV 2014		
Mould No: 7	Tooling: Full Size		