



This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
 This drawing becomes an uncontrolled document once issued as hard or electronic copy.
 Customer to confirm current revision of drawing prior to ordering.


END VIEW



PLAN VIEW



SIDE VIEW



- Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
 2. All sharp edges removed for safe handling
 3. Anode insert material to meet relevant Australian/International specifications

Chemical Composition Limits		Alloy:
Standard: AS2239* (Most current revision)		Z1
Zinc		
Element	min.	max.
Cadmium	0.025	0.07
Aluminium	0.10	0.50
Silicon	-	0.005
Copper	-	0.005
Iron	-	0.005
Lead	-	0.006
Other Impurities		
- each	-	0.005
- total	-	0.02
Zinc	remainder	

C D Q
 CAST INDENTATION LETTERING

All dimensions are in mm (nominal)



Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
20.5	20.6

Rev	Details of Change(s)	Date	Drawn	Verified
1	For manufacture	02JUL14	<i>BL</i>	<i>BL</i>

CAA
 Cathodic Anodes Australasia
 cathodicanodes.com.au

Product Zinc Anode		Scale 1 to 5
Part no. CDZ8-24-200H		Rev Sheet 1 1 of 1
Drawing no. CD1710		Drawn by: BL Verified by: JL Date: 02JUL14
Mould no. 10		

* Corresponds to MIL-DTL-18001L alloy composition