


Fernstrum 1404B

This drawing is the property of Cathodic Anodes Australasia. To be used with permission only. This drawing becomes an uncontrolled document once issued as hard or electronic copy. Customer to confirm current revision of drawing prior to ordering.



2 x 14.3 Holes @ 57 Centres
 DRILL ZINC BLOCK
 NO INSERT(S)

PART NO. 1404B COLOUR - YELLOW 0.75# EA, 2# PER SET BN4U-E1, BN6 & BN6U MILLIMETERS SHOWN ARE ROUNDED

Chemical Composition Limits			Alloy: Z1
Standard: AS2239* (Most current revision)			
Zinc			
Element	min.	max.	
Cadmium	0.025	0.07	
Aluminium	0.10	0.50	
Silicon	-	0.005	
Copper	-	0.005	
Iron	-	0.005	
Lead	-	0.006	
Other Impurities			
- each	-	0.005	
- total	-	0.02	
Zinc	remainder		

* Corresponds to MIL-DTL-18001L alloy composition

- Notes
- Anodes are cast to comply with CAA's standard casting tolerances
 - All sharp edges removed for safe handling
 - Anode insert material to meet relevant Australian/International specifications



Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
0.34	0.34

CAA
Cathodic Anodes Australasia
cathodicanodes.com.au

Rev	Details of Change(s)	Date	Drawn	Verified
1	Cathodic Diecasting Original	15 February 2012	R.N.	R.G.
2	2013 Catalogue Version (CAA Logo)	29 April 2014	R.N.	R.G.

Product Zinc Anode Fernstrum 1404B	
Part no. CDZ2-42-375H Type 2	Scale 1.5 : 1
Drawing No: CD3263	Rev Sheet 2 1 of 1
Drawn by: R Northey Date: 29 APR 2014	
Mould No: 6 Tooling: Blank Ends	