This drawing is the property of Cathodic Anodes Australasia. To be used with permission only.
This drawing becomes an uncontrolled document once issued as hard or electronic copy.
Customer to confirm current revision of drawing prior to ordering.



Notes
1. Anodes are cast to comply with CAA's standard casting tolerances
2. All sharp edges removed for safe handling
3. Anode insert material to meet relevant Australian/International specifications

Chemical Composition Limits Standard: AS2239*(Most current revision) Zinc		Alloy: **Z1**
Element	min.	max.
Cadmium	0.025	0.07
Aluminium	0.10	0.50
Silicon	-	0.005
Copper	-	0.005
Iron	-	0.005
Lead	-	0.006
Other Impurities		
- each	-	0.005
- total	-	0.02
Zinc	remainder	

* Corresponds to MIL-DTL-18001L alloy composition



Rev	Details of Change(s)	Date	Drawn	Verified
1	For Manufacture	19 AUG 13	R.N.	R.G.

Nett Weight Kg (nominal)	Gross Weight Kg (nominal)
8.00	**8.25**

Cathodic Anodes Australasia

cathodicanodes.com.au

AUSTRALIAN MADE

All dimensions are in mm (nominal)

Product: **Zinc Anode**

Part no.: **CDZ8-126-1.50H Type 2**

Scale: **1 : 2**

Drawing No: **CD3636**

Rev: **1**

Sheet: **1 of 1**

Drawn by: R Northey

Date: 19 AUG 2013

Mould No: 96

Strap Sample: 55